

More than 32 years of experience

C1 Maxi designed for vineyards with very high loads and a high height above ground  
Recommended for total height between 2.30 to 3.00 mtr in thickness 1.80/2.00/1.95/2.15 mm

### Main Advantages

- ◆ Profiling without any angle in order not to damage during mechanical contacts
- ◆ Special cross section to protect the open side of the post (60 x 40 mm – 2.36'' x 1.57'')
- ◆ Optimal compromise between flexibility and high mechanical strength
- ◆ Strong ability to install in difficult soil
- ◆ Side 40 mm to optimize the stability of the trellising
- ◆ Special shape of the hooks to avoid closure during the mechanical harvest
- ◆ Wire in contact with the internal structure of the post
- ◆ Double hook for the wires during the soil cultivation



### Galvanization

| C1 Maxi                                   | Strip Galva<br>Z 275 gr/m2<br>18-25μ per side<br>En 10 142<br>Steel DX51-S250 GD |                           |                          | Cor-ten B type<br>Steel S300JOWP |                           |                          | Hot dip galvanization<br>En 1461<br>60-80μ per side<br>Steel S235 JR En 10 025/En 10 147 |                          |                          |
|-------------------------------------------|----------------------------------------------------------------------------------|---------------------------|--------------------------|----------------------------------|---------------------------|--------------------------|------------------------------------------------------------------------------------------|--------------------------|--------------------------|
| C1 Maxi per bundles<br>100 pces /Coil 135 | Thickness 1.50<br>0.059"                                                         | Thickness 1.80<br>0.0709" | Thickness 2.00<br>0.078" | Thickness 1.60<br>0.063"         | Thickness 1.80<br>0.0709" | Thickness 2.00<br>0.078" | Thickness 1.65<br>0.064"                                                                 | Thickness 1.95<br>0.076" | Thickness 2.15<br>0.084" |
| Weighting per mtr                         | 1.59                                                                             | 1.91                      | 2.11                     | 1.70                             | 1.91                      | 2.11                     | 1.75                                                                                     | 2.10                     | 2.32                     |

### Type of hooks (option A or N on demand)

- ◆ **A Type**  
To easily remove and replace the moving wires
- ◆ **N Type**  
Wires in a fixed position
- ◆ **H Type**  
Winter position wires



### Installation advice

- ◆ Cap and mini piston on request
- ◆ Plant the post during the wet season
- ◆ Drive 25-30 % of the post length into the ground
- ◆ Deep rip soils during site preparation
- ◆ Drill a pilot hole in difficult ground
- ◆ Adaptation of the inter-distance between the posts in particular (windy area-high production in hectoliter-high degree of mechanization)

#### **Consortium France**

Jean-Luc Duboeuf  
4381 Route Du Tremblay  
F-73 290 La Motte Servolex  
Tel : +33 615 93 14 99  
[jl.duboeuf@consortium73.fr](mailto:jl.duboeuf@consortium73.fr)

#### **Consortium S.p.A**

Viale Dell'Industria, 26  
I - 37038 Soave Verona Italia  
Tel : +39 045 610 28 88  
[info@consortiumspa.net](mailto:info@consortiumspa.net)